WOLFPACK X system

CLx Series / HD Active Night Vision Cameras



Models:

EW-CL3x13

Field-of-View (diagonal):

13°

EW-CL3x21

Field-of-View (diagonal):

21°

EW-CL3x37

Field-of-View (diagonal):

... ..

EW-CL3x55

Field-of-View (diagonal):

55°

EW-CL3x86

Field-of-View (diagonal):

86

Near Infrared optimized low-light CMOS sensor.

High resolution video in zero-light environments using built-in infrared illuminator.

· Advanced image processing for exceptional low-noise image quality.

• User configurable 4x/6x/8x electronic zoom w/ image pan.

· Still image and full motion video capture and store.

· Five available camera focal lengths.

Built-in articulation provides 280° range-of-motion.

300° camera head rotation for correct image orientation in any position.

Specifications:

Camera Type: Near infrared optimized low-light CMOS sensor

Sensitivity: 0.0002 lux

Resolution: 1920 (H) x 1080 (V) pixels **Field-of-View (diagonal):** 13°, 21°, 37°, 55°, 86°

Illumination: 940nm near infrared w/8 high intensity LEDs

Connector: Eomax high durability quick-release

Environmental: IP67 submersible

Dimensions (incl articulation): 200mm x 43mm (H) x 44mm (W)

Weight: 155g

Operating Temperature: -30°C to 60°C
Storage Temperature: -40°C to 80°C

